

MegaTwin Dyneema®

Cable pull

All-rounder at the highest level. Top breakload, lowest elongation and maximum life expectancy.



Performance

Competition line made with Dyneema® SK 78 fibres for extreme strength and minimal elongation.



Does it all

Highly flexible polyester cover for excellent all-round characteristics and optimal grip on the core in cleats.



Durability

Robust and durable due to the best raw materials and an extremely proven design.

Diameter

2 mm - 36 mm Ø

Construction



Technical data

Elongation at 10% of the breaking load: 0.40 %

Ø [mm]	Weight [kg/100 m]	Bl. real in splice [kN]	Bl. linear DIN according to EN ISO 2307 [kN]
2 mm Ø	0.00	0.00	0.00
3 mm Ø	0.00	0.00	0.00
4 mm Ø	0.00	0.00	0.00
5 mm Ø	0.00	0.00	0.00
6 mm Ø	2.60	16.50	18.30
8 mm Ø	4.00	28.00	31.10
10 mm Ø	7.00	49.00	54.40
12 mm Ø	9.90	70.00	77.80
14 mm Ø	13.00	85.00	94.40
16 mm Ø	17.50	120.00	133.00
18 mm Ø	23.70	150.00	167.00
20 mm Ø	28.00	200.00	222.00
22 mm Ø	31.00	230.00	256.00
24 mm Ø	35.00	245.00	272.00
26 mm Ø	41.00	285.00	317.00
28 mm Ø	44.00	340.00	378.00
30 mm Ø	53.00	400.00	444.00
32 mm Ø	0.00	0.00	0.00
36 mm Ø	0.00	0.00	0.00

Gleistein

More than Ropes.

