

Allround MegaLoop

Industrial lift

The endless rope. The universal Allround MegaLoop sets new standards for round slings.



New handling standard

Maximum work safety thanks to minimal weight and round cross-section.



New versatility standard

Fits all attachment points, but can be safely doubled up as well.



New performance standard

Round-wound high-performance core, indestructible braiding cover, highest precision in strength and length.

Technical data

Elongation at 10% of the breaking load: 0.60 %

7:1 (Europe)

WLL direct [t]	WLL choke [t]	WLL basket [t]	Ø [mm]	Bearing surface under load [mm]	Thickness with optimum support [mm]
5	4	10	18	25	10
10	8	20	24	32	20
20	16	40	34	52	25
30	24	60	46	78	35

5:1 (metric tons)

WLL direct [t]	WLL choke [t]	WLL basket [t]	Ø [mm]	Bearing surface under load [mm]	Thickness with optimum support [mm]
7	5.6	14	18	25	10
14	11.2	28	24	32	20
28	22.4	56	34	52	25
42	33.6	84	46	78	35

5:1 (US tons)

WLL direct [t]	WLL choke [t]	WLL basket [t]	Ø [mm]	Bearing surface under load [mm]	Thickness with optimum support [mm]
7.7	6.2	15.4	18	25	10
15.4	12.3	30.8	24	32	20
30.6	24.6	61.6	34	52	25
46.2	37.0	92.4	46	78	35

Gleistein

More than Ropes.

