CruiseTail Mooring

Up on top: high-quality, durable tail with handling edge.



Buoyant

Round braid made of light Plus yarns endlessly spliced as a grommet



Durable

Overbraided stretch zone and eye protection with additional impregnation



Uncomplicated

Best handling due to the bundled braiding of the two rope strands

Diameter

82 mm - 202 mm Ø





Technical data

Elongation at 10% of the breaking load: 1.80 %

Ø [mm]	Weight [kg/100 m]	Bl. real in splice [kN]	Bl. linear DIN according to EN ISO 2307 [kN]
82 mm Ø	211.80	374.40	416.00
90 mm Ø	243.60	456.00	507.00
98 mm Ø	311.80	558.40	620.00
106 mm Ø	369.10	656.10	729.00
114 mm Ø	426.40	760.00	844.00
122 mm Ø	497.30	888.00	987.00
130 mm Ø	560.90	1,001.70	1,113.00
138 mm Ø	637.30	1,136.00	1,262.00
146 mm Ø	704.60	1,262.40	1,403.00
154 mm Ø	800.00	1,431.90	1,591.00
170 mm Ø	975.50	1,760.00	1,956.00
186 mm Ø	1,182.70	2,128.00	2,364.00
202 mm Ø	1,406.40	2,520.00	2,800.00





