

# GeoSquare<sup>®</sup> Polyamide

Mooring

**Best cushioning, best spliceability. Square-braided mooring line with outstanding shock absorption characteristics.**



## Highest comfort

Premium polyamide mooring line with highest stretch



## Strong and light

Very high strength at low weight



## Handling

Easy to splice, grippy surface, torsion neutral

### Diameter

20 mm - 96 mm Ø

### Construction



## Technical data

Ø [mm]	Weight [kg/100 m]	Bl. real in splice [kN]	Bl. linear DIN according to EN ISO 2307 [kN]
20 mm Ø	24.70	84.00	93.30
22 mm Ø	29.90	105.00	117.00
24 mm Ø	35.50	124.00	138.00
26 mm Ø	41.70	145.00	161.00
28 mm Ø	48.40	168.00	187.00
30 mm Ø	55.50	190.00	211.00
32 mm Ø	63.20	215.00	239.00
40 mm Ø	98.70	330.00	367.00
44 mm Ø	119.00	400.00	444.00
48 mm Ø	142.00	475.00	528.00
52 mm Ø	167.00	555.00	617.00
56 mm Ø	193.00	638.00	709.00
60 mm Ø	222.00	730.00	811.00
64 mm Ø	253.00	830.00	922.00
68 mm Ø	286.00	937.00	1,041.00
72 mm Ø	320.00	1,035.00	1,150.00
80 mm Ø	395.00	1,276.00	1,418.00
88 mm Ø	478.00	1,540.00	1,711.00
96 mm Ø	569.00	1,830.00	2,033.00

# Gleistein

More than Ropes.

