

GeoTwin[®] Polyester

Superyacht

Permanently flexible, durable mooring line with balanced characteristics for large yachts.



Comfort

Permanently flexible with balanced elongation properties for comfortable mooring.



Quality

Abrasion-resistant polyester double braid with long service life and very high strength.



Remains dry

Water-repellent, high-quality mooring line for exacting demands.

Diameter

20 mm - 48 mm Ø

Construction



Colors



Technical data

Elongation at 10% of the breaking load: 2.00 %

Ø [mm]	Weight [kg/100 m]	Bl. real in splice [kN]	Bl. linear DIN according to EN ISO 2307 [kN]
20 mm Ø	30.00	85.00	94.40
22 mm Ø	37.30	99.00	110.00
24 mm Ø	43.40	115.00	128.00
26 mm Ø	51.00	135.00	150.00
28 mm Ø	59.00	158.00	176.00
30 mm Ø	68.00	178.00	198.00
32 mm Ø	78.00	198.00	220.00
36 mm Ø	99.00	262.00	291.00
38 mm Ø	110.00	285.00	317.00
40 mm Ø	121.00	326.00	362.00
44 mm Ø	147.00	380.00	422.00
48 mm Ø	177.00	455.00	506.00

Gleistein

More than Ropes.