

TowMaster towing

Achieving more together: seven braided cores, a protective cover – extremely durable towing line with perfect shock absorption characteristics.



Does it all

High-strength polyester multi-core rope with right level of stretch



Durable

Extremely abrasion-resistant cover provides protection and stability



Torsion protection

Longitudinal stripes make twists in the rope immediately visible

Diameter

56 mm - 168 mm Ø

Construction



Technical data

Elongation at 10% of the breaking load: 1.60 %

Ø [mm]	Weight [kg/100 m]	Bl. real in splice [kN]	Bl. linear DIN according to EN ISO 2307 [kN]
56 mm Ø	239.00	905.00	1,006.00
60 mm Ø	275.00	1,090.00	1,211.00
64 mm Ø	315.00	1,230.00	1,367.00
68 mm Ø	352.40	1,350.00	1,500.00
72 mm Ø	395.00	1,500.00	1,667.00
76 mm Ø	441.00	1,800.00	2,000.00
80 mm Ø	489.00	1,850.00	2,056.00
84 mm Ø	548.00	2,040.00	2,267.00
88 mm Ø	590.00	2,220.00	2,467.00
96 mm Ø	702.00	2,650.00	2,944.00
104 mm Ø	825.00	3,100.00	3,444.00
112 mm Ø	956.00	3,580.00	3,978.00
120 mm Ø	1,100.00	4,100.00	4,556.00
128 mm Ø	1,250.00	4,640.00	5,156.00
136 mm Ø	1,410.00	5,240.00	5,822.00
144 mm Ø	1,580.00	5,850.00	6,500.00
152 mm Ø	1,760.80	6,500.00	7,222.00
160 mm Ø	1,951.00	7,180.00	7,978.00
168 mm Ø	2,151.00	7,900.00	8,778.00

Gleistein

More than Ropes.

