

X-Twin HS Dyneema® SSC-Cover towing

With full force: extremely compact and buoyant high-performance towing line with lowest elongation and the unsurpassed durability of the SSC cover



Ultimate strength

Core made of heat-set Dyneema® SK78



Abrasion resistant

Exceptionally abrasion-resistant SSC cover from sub-braids made with Dyneema®



Handling

Extremely light and compact ensuring exemplary handling

Diameter

40 mm - 68 mm Ø

Construction



Technical data

Ø [mm]	Weight [kg/100 m]	Bl. real in splice [kN]	Bl. linear DIN according to EN ISO 2307 [kN]
40 mm Ø	104.90	1,298.00	1,442.00
42 mm Ø	123.50	1,411.00	1,568.00
44 mm Ø	142.30	1,700.00	1,889.00
46 mm Ø	161.20	1,988.00	2,209.00
48 mm Ø	171.30	2,132.00	2,369.00
50 mm Ø	182.80	2,266.00	2,518.00
52 mm Ø	196.60	2,400.00	2,667.00
56 mm Ø	224.10	2,678.00	2,976.00
62 mm Ø	260.90	2,812.00	3,124.00
64 mm Ø	276.70	2,946.00	3,273.00
66 mm Ø	302.80	3,214.00	3,571.00
68 mm Ø	323.90	3,337.00	3,708.00

Gleistein

More than Ropes.

