


GeoLink shackles are light and flexible, can be opened and closed quickly without the need for any additional equipment and are self-locking under load.


Diameter

8 mm - 14 mm Ø

Construction



Colors



Technical data

Elongation at 10% of the breaking load: 0.60 %

Ø [mm]	Weight [kg/100m]	Bl. real in splice [kN]	Total length in closed state [mm]
4 mm Ø	0.01	6.70	85
8 mm Ø	0.01	14.00	110
10 mm Ø	0.01	24.00	110
12 mm Ø	0.02	31.90	125
14 mm Ø	0.04	55.90	150
18 mm Ø	0.07	79.80	175
20 mm Ø	0.14	119.50	200
24 mm Ø	0.28	167.50	350
28 mm Ø	0.37	191.50	400
32 mm Ø	0.55	243.00	450
34 mm Ø	0.80	308.50	500
36 mm Ø	1.03	360.00	550
40 mm Ø	1.36	437.00	600
44 mm Ø	1.61	477.00	650
48 mm Ø	2.14	577.50	700
50 mm Ø	2.60	634.00	750
54 mm Ø	2.98	654.00	800
58 mm Ø	3.58	742.00	850
60 mm Ø	4.33	830.00	900
64 mm Ø	5.08	922.50	950
68 mm Ø	5.73	950.40	1,000
74 mm Ø	7.98	1,203.80	1,100
82 mm Ø	10.08	1,390.00	1,200
90 mm Ø	13.65	1,650.00	1,500
94 mm Ø	18.86	1,925.00	1,500
96 mm Ø	23.49	2,225.00	1,800